Token Dispenser RESET API

Connecting HEXTEK token dispenser on your WiFi network

1. Turn ON token dispenser then WiFi on your mobile/computer, find WiFi AP name HEXTEK-PrinterAP as shown on image.1



image.1

2. Select HEXTEK-Printer AP then it will show further menus as given on image.2.



image.2

<

3. Select **Configure WiFi**, it will list all available nearby WiFi names as given on image.3

3:30 💎 📥 🔹 🛠 🐨 🗰 🖌	🖞 R 🚾 🛋 🗎 45%
Sign in to HEXTEK-PrinterAP 192.168.4.1	
HP-Print-B0-LaserJet Pro MFF COFE_DEC4	2 92% ● 54%
SSID	
password	
N	
save	
<u>Scan</u>	
<	

image.3

4. Select your WiFi name enter it's password, now dispenser will be connected on your WiFi network.

Note: if given WiFi credentials are correct token dispenser will be connected on your network otherwise HEXTEK-PrinterAP signal will appear again.

RESET API

Open any web browser enter following GET request to test token dispenser

I) To sent & print token number 5 ----->Dispenser IP/get-token?token=5

Note: Verify to your WiFi network to find out IP address of token token dispenser

II) To set token dispenser date time ----->Dispenser IP/get-datetime?datetime=12/05/21 12:45:25

III) To view last printed token number and its date & time ---- > Token dispenser IP/get-report

Include above RESET API on your software to handle/control our token dispenser